

Output Technology's PrintCenter™ 45 printer has just widened your choices in continuous form non-impact printers. The PrintCenter™ 45 brings flexible printing solutions to many diverse business printing environments. This new printer provides impressive print speeds of 45 ppm (3,000 lpm) when printing full 11" x 16" continuous forms. The PrintCenter™ 45 utilizes flash fusing technology enabling printing on a wide variety of media including pressure sensitive labels. With its straight paper path, 500,000 pages per month duty cycle and integrated refolder, the PrintCenter™ 45 provides outstanding jam-free printing for your mid-range production printing requirements.



PrintCenter™ 45

- Printing speeds up to 3000 lines per minute
- Forms overlay printing
- Automatic forms loading / 1st page printing
- Flat paper path for jam free operation
- Flash fusing for printing on heat sensitive media
- Integrated Gravity Stacker

PrintCenter™ 45

MODEL

PrintCenter45

PRINT SPEED

3000LPM at 6LPI
(H) (W)
11" x 8.5" - 45ppm
11 x 14 ^{7/8} - 45ppm
8.5" x 11" - 58ppm
8.5" x 14" - 58ppm

PRINTING METHOD

Electro photography process
LED array

TONER

Single part dry toner

TONER FUSING

Xenon flash fusing

WORKLOAD

500,000 pages per month

RESOLUTION

300 X 300 dpi

PAPER HANDLING

Continuous 1-part tractor fed,
16 lb bond to 115 lb index
60 ~ 204 g/m²

MAXIMUM PAPER SIZE

20" (H) x 16" (W)

MAXIMUM PRINT AREA

20" (H) x 14.6" (W)

COMPATABILITY

Emulations
HP PCL, Epson ESC/P, UL-PC Printer
Language, Windows

Drivers

Windows 95, 98, NT, 2000 & XP.

FONTS

PCL fonts compatible (70 AGFA Intelli-
fonts)

SPECIAL SYMBOLS

UL-PC Emulation
OCR-B Font
BAR Code: Code 25, Code 39, UPC/
EAN Code, Codabar
Dynamic Bar Code: Code 25, Code 39,
Code 128
PDF417

CONTROLS

Graphic LCD pane

POWER REQUIREMENTS

200-240vac/50-60Hz
Single Phase 3 Wire

POWER CONSUMPTION

4500W (max) 300W (standby)

OPERATING ENVIRONMENT

10 ~ 30 C / 30 ~ 80% RH

ACOUSTIC

70 dBA printing 55 dBA idle

SYSTEM ENVIRONMENT

DOS, UNIX, NOVEL, OS/2, MS Windows
and others.

INTERFACES

Parallel (IEEE-P 1284), TCP/IP
Print Controller
Optional
External Twinax / Coax

PHYSICAL

Weight

Approximately 550 lbs (240 KG) including
stacker

Dimensions

80.5 cm (W) x 125 cm (H) x
85 cm (D)
32" x 50" x 34"

PRINTING FUNCTIONS

Rotate, enlarge draw line, draw circle,
pan, reverse, background, wordgap,
linegap, grid, frame, upperline, underline,
portrait, landscape, cursor moving, form
overlay, text and image overlay printing,
CPI, LPI, and LPP selection windows
printing.

PAPERSTACKER

Integrated 3000 page capacity powered
gravity stacker

Specifications subject to change without notice.



Corporate Office
3808 N. Sullivan Rd. Bldg #3
Spokane, WA 99216-1619
509-536-0468
800-468-8788 (USA Only)
FAX: 509-533-1285

GSA Contract # GS-35F-0328J—Printers/Accessories
GSA Contract # GS-14F-0669G—Ribbons

All company and product names are trademarks of their
respective owners.

060-00299-01 Rev 2

www.output.com